

Desktops



Desktop Size Industrial Performance

Featuring the
CLP 521, CLP 621 and CLP 631
CLP 521Z, CLP 621Z and CLP 631Z
Available in white and dark grey cases

Available in Indonesia from:

Labeltronics
For all your labelling needs

Jl. Logistik No. 53

Pegangsaan Dua - Jakarta 14260

Telp: 021-4483-4423 / 34 / 61

Fax: 021-4483-5452

sales@labeltronics-id.com

www.labeltronics-id.com

CITIZEN
Micro HumanTech

Peeler Tech Specs

Fits	CLP 521, 621, 631 + Z models
Type	S-bend dual roller
Roller Type	Silicone rubber
Liner Thickness	0.0027 inches, 0.07mm (max)
Label Thickness	0.0067 inches, 0.17mm (max)
Liner Width	1 inch, 25.4mm (min)
Liner Width	4.65 inches, 118mm (max)
Label Length	1 inch, 25.4mm (min)
Label Length	4.72 inches, 120mm (max)
Label width	To be narrower than liner
Number of Labels	100 Km or 1 million peeled labels (when using specified media)
Present Sensor	Infrared reflection diode
Size (WxDxH)	145 x 37 x 39 (uninstalled)
Weight	0.26 Kg (approx)

Cutter Tech Specs

Fits	CLP 521, 621, 631 + Z models	
Type	Guillotine	
Media Thickness	0.0024 inches, 0.06mm (min)	
Media Thickness	0.01 inches, 0.25mm (max)	
Cut Length	Minimum: 1.00 inch, 25.4 mm Maximum: determined by software	
Number/Cuts Media thickness	300,000 cuts 0.06-0.15mm	100,000 cuts 0.15-0.25mm
Type of Media	Card or ticket media, Adhesive labels (Cut quantity may not be guaranteed with adhesives) Fanfold or Roll media. (Roll media should be on a minimum 50mm core.)	
Cut tolerance	± 1 mm horizontal + vertical	
Size (WxDxH)	149 x 51 x 76 (uninstalled)	
Weight	0.49 Kg (approx)	

Contact Information

We have many label size ready in stock for you to order in small quantity.
Please contact for details.

Tech Specs

Models	CLP 521 CLP 521Z	CLP 621 CLP 621Z	CLP 631 CLP 631Z
Technology	Direct Thermal	Thermal Transfer & Direct Thermal	
Resolution	203 dpi (8 dots/mm)		300 dpi (12 dots/mm)
Max Print Speed	4 inches / sec, 100 mm / sec		
Max Print Width	4.10 inches, 104.1 mm		
Max Media Width	4.65 inches, 118.1 mm		
Min Media Width	1.00 inches, 25.4 mm		
Max Roll Size	5 inches, 125 mm outside diameter (internal) 8 inches, 200 mm outside diameter (external option)		
Min Core Size	1.0 inch, 25 mm core		
Media Sensor	Fully adjustable		
Media Thickness	0.0025 - 0.01 inches, 0.635 - 0.254 mm		
Ribbon Size (OD)	Not applicable - direct thermal only	2.9 inches, 74 mm	
Ribbon Length		Nominally 360m length	
Ribbon Winding		Ink side in or out, switch selectable	
Ribbon Type		Wax, Wax/Resin or Resin Type	
Ribbon System		ARCP™ automatic ribbon tension adjustment	
Standard Interfaces	Parallel (IEEE-1284), Serial (RS-232C), USB		
Optional Interfaces	Ethernet (10/100 BaseT), Wireless LAN (802.11b)		
Case Type	Hi-Open™ plastic case		
Mechanism Type	Hi-Lift™ metal mechanism		
Control Panel	4 buttons and 4 LEDs		
RAM Memory	8.0 Mb total, 0.5 Mb available for user		
Flash (NV) Memory	2.0 Mb total, 0.5 Mb available for user		
Emulations (Languages)	CLP 521, 621, 631: Datamax® I-Class™, DMX400™, Prodigy Plus® CLP 521Z, CLP 621Z, CLP 631Z: Zebra® ZPL-II®		
Windows® drivers	Free-of-charge on CD with printer		
Label Design Software	Including support for Windows® Vista™		
Size (W x D x H)	231 x 289 x 183mm	231 x 289 x 270 mm	
Weight (approx)	7.9lbs, 3.6 kg	9.9lbs, 4.5 kg	
Printer Warranty	2 Year Manufacturer's Warranty		
Print Head Warranty	30 Kms or 6 months	50 Kms or 6 months	

Supplier Information

Labeltronics

For all your labelling needs

Jl. Logistik No. 53

Pegangsaan Dua - Jakarta 14260

Telp: 021-4483-4423 / 34 / 61

Fax: 021-4483-5452

sales@labeltronics-id.com

www.labeltronics-id.com